

## VAIIVA A/T TIRE SIZES AND SPECIFICATIONS

Series	Size	Side Wall	Load Index	Product Code	Weight Lbs	Rim Width		Overall Diameter	Overall Width	Tread Depth (32nd)	Revolutions Per Mile	
						Approved	Measuring				Km	Mile
75	205/75R15	OWL	97S	T444720	23.8	5-6.5	5.5	27.1	7.9	14	479	771
	215/75R15	OWL	100S	T444722	26.7	5.5-7	6.0	27.7	8.5	14	470	757
	225/75R15	OWL	102S	T444724	28.2	6-7	6.0	28.3	8.8	14	458	737
	235/75R15	OWL	105S	T444702	30.6	6-7.5	6.5	28.9	9.2	14	449	723
	235/75R15 XL	OWL	109S	T444726	32.2	6-8	6.5	28.9	9.2	14	449	723
	235/75R16	OWL	108S	T444750	33.0	6-8	6.5	29.8	9.3	14	438	700
	245/75R16	OWL	109S	T444710	35.5	6.5-7.5	7.0	30.5	9.8	14	425	685
	265/75R15	OWL	112S	T444728	38.8	7-8.5	7.5	30.7	10.5	15	423	681
	265/75R16	OWL	114S	T444730	40.4	7-8.5	7.5	31.7	10.5	15	410	660
	70	225/70R14	OWL	98S	T444732	26.5	6-7	6.5	26.5	8.9	13	494
225/70R15		OWL	100S	T444752	27.0	6-7.5	6.5	27.5	9.0	13	477	763
225/70R16		OWL	101S	T444738	32.4	6-7	6.5	28.4	8.9	14	457	736
235/70R15		OWL	102S	T444734	30.0	6-8	7.0	28.0	9.5	13	464	747
235/70R16		OWL	104S	T444740	33.3	6-8	7.0	29.0	9.5	14	448	721
235/70R17 XL		OWL	111S	T444756	34.0	6-8	7.0	30.0	9.5	14	433	697
245/70R16		OWL	107S	T444742	35.0	6.5-8	7.0	29.5	9.8	14	439	707
245/70R17		OWL	110S	T444758	35.0	6.5-8	7.0	30.4	10.1	14	424	683
255/70R16		OWL	109S	T444744	36.9	6.5-8.5	7.5	30.1	10.2	14	432	695
255/70R17		OWL	112S	T444797	38.0	6.5-8.5	7.5	31.1	10.2	14	417	671
265/70R15		OWL	112S	T444736	37.2	7-9	8.0	29.6	10.6	14	438	706
265/70R16		OWL	111S	T444746	38.5	7-9	8.0	30.6	10.7	14	425	685
265/70R17		OWL	113S	T444748	40.5	7-9	8.0	31.7	10.7	14	412	664
265/70R18		OWL	116S	T444798	42.0	7-9	8.0	32.6	10.7	14	395	636
65	235/65R17	OWL	104T	T444760	33.0	6.5-8.5	7.0	29.1	9.5	14	445	716
	245/65R17	OWL	107S	T444754	34.0	7-8.5	7.0	29.6	9.6	14	440	704
	255/65R17	OWL	110S	T444762	35.0	7-9	7.5	30.1	9.9	14	432	695
	265/65R17	OWL	112T	T444764	38.0	7.5-9.5	8.0	30.6	10.7	14	424	682
	275/55R20 XL	OWL	117S	T444801	46.0	7.5-9.5	8.5	31.9	12.7	13	406	654
85	LT31x10.5R15 C	OWL	109Q	T444706	41.3	7-9	8.5	30.3	10.5	17	427	688
	LT215/85R16 E	SBW	115/112Q	T444954	39.0	5.5-7	6.0	30.3	9.1	17	426	686
80	LT235/85R16 E	SBW	120/116Q	T444700	42.7	6-7	6.5	31.8	9.4	17	410	661
	LT235/80R17 E	OWL	120/117R	T444766	41.0	6-7.5	6.5	31.7	9.3	17	408	657
75	LT225/75R16 E	SBW	115/112Q	T444708	40.6	6-7	6.0	29.5	8.8	17	442	712
	LT235/75R15 C	OWL	104/101Q	T444704	35.9	6-7	6.5	28.9	9.0	16	449	723
	LT245/75R16 E	SBW	120/116Q	T444712	44.3	6.5-7.5	7.0	30.5	9.6	17	427	688
	LT245/75R17 E	OWL	121/118S	T444796	46.0	6.5-7.5	7.0	31.5	9.8	16	410	660
	LT265/75R16 C	OWL	112/109Q	T444714	46.5	7-8	7.5	31.7	10.4	17	410	660
	LT265/75R16 E	OWL	123/120Q	T444716	49.8	7-8	7.5	31.7	10.6	17	410	660
	LT285/75R16 D	OWL	122/119Q	T444718	54.8	7.5-9	8.0	32.8	11.5	17	397	640
	LT315/75R16 D	OWL	121Q	T444776	62.0	8-10	8.5	34.8	12.9	17	375	603
70	LT265/70R17 E	OWL	121/118R	T444772	48.0	7-8.5	8.0	31.7	10.7	17	409	659
	LT275/70R17 C	OWL	114/110R	T444770	49.0	7-8.5	8.0	32.1	11.1	17	402	647
	LT275/70R18 E	OWL	125/122S	T444795	54.0	7-8.5	8.0	33.2	11.0	16	390	627
	LT285/70R17 D	OWL	121/118R	T444768	54.8	7.5-9	8.5	32.7	11.5	17	395	636
	LT305/70R16 D	OWL	118/115Q	T444774	56.0	8-9.5	9.0	32.8	12.2	17	397	639
65	LT275/65R18 E	OWL	123/120S	T444793	52.0	7.5-9.5	8.0	32.1	11.0	16	402	647